

## Product Feature:

- Professional In-Vehicle power design, 9-32V DC Wide Voltage Range
- Built-in ultracapacitor, avoid data loss and sd card damage caused by sudden outage
- Support SD card storage, maximum 256G
- 4CH local recording with 720P resolution in real time
- GPS Supported
- Supports 4G/3G/2G



Model	VIN-9504-TG
Operating system	Embedded Linux OS
Video & Audio compression	H.264 for Video / G.726 for Audio
Resolution	PAL / NTSC:1280x720
Compound mode	4ch 720P/4ch 960H/2ch 720P+2ch 960H
Upgrading method	USB Disk
AV Input	4ch aviation interface
AV Output	1ch VGA video output, 1ch aviation AV output
Alarm input / Output	4 digital inputs (2 Positive trigger, 2 negative trigger) / 1 output
SD card	1 SDXC High speed card (up to 256G)
USB interface	1 USB 2.0 (support U disk/mouse)
Ignition input	1 ACC signal
SD Card Lock	Supported with Key
Interface	1 LVTTTL
Storage Media	SD card storage
GPS	Supported
4G/3G/2G	Supports
Power input	9~32V DC
Power Output	12V 300mA
Power consumption	Standby 3mA Maximum consumption 18W @12V 1.5A @24V 0.75A
Working temperature	-20 --- 70℃

**Vintron Informatics Ltd.** Vintron is constantly developing and improving products. We reserve the right to modify products and specification without notice.