



Product Feature:

- 1/3" HD-CMOS
- CS Lens 8mm(12mm Optional)
- IR Distance up to 80-100Mtr.
- IR Bullet Camera
- 6-IR Array LED / up to 80-100Mtr...
- PoE Optional
- H.265 / H.264 Supported

SPECIFICATION

| Model | VIN-IP-L14-408IBAR6-A6 |
|---------------------|---|
| Image Sensor | 1/3" HD-CMOS |
| Lens Mount | CS lens 8mm (12mm Optional) |
| Minimum Illumintion | 0.5 Lux; 0Lux With IR on |
| P2P | Supported |
| Video Compression | H.264 Video Compression, Support Dual Stream |
| Frame Rate | 4.0 Megapixel @ 19FPS |
| Image Output | Main Stream:2560x1440@1-19fps / Sub Stream: 720x480@1-25fps |
| Shutter Speed | Auto/Manual, 1/25 ~ 1/10,000s |
| White Balance | Auto |
| ONVIF | Yes |
| Network Interface | 1RJ45 Ethernet Interface |
| Network Function | Free Client Software |
| IR Distance | 6-IR Array LED / Up to 80-100Mtr. |
| Working Condition | -10°C to +55°C (32°F-133°F) , 10% - 90%PH |
| Power Supply | 12VDC / 2A |

Vintron Informatics Ltd. Vintron is constantly developing and improving products. We reserve the write to modify products and specification without notice.