

Product Feature:

- 2.0MP CMOS sensor
- Support for mobile video surveillance (iOS, android)
- Clear and bright industry leader
- Support multiple display modes (traditional mode, mixed mode, corridor three-dimensional picture scroll mode, and panoramic inversion mode)
- Comes with AP hot spots; no wireless router can control



Model	VIN-IP-L17-FE-108
Embedded Processor	GM8135S
sensor	Sc2135
Lens	1/2.5 Fisheye lens, f=1.44mm
View angle	360°
Image pixels	2MP
Minimum illumination	4500mV/Lux-s 0.01Lux@F2.0,black/white 0.001Lux@F2.0
Day and night	IR-cut double filter automatic switching
Video coding	H.264, dual stream
Video frame rate	25frame/second
Image resolution	Max: 1920x1080
Audio coding	ADPCM, support two way voice intercom
Network Interface	Rj45 10M/100M
Wireless standard	IEEE802.11b/g/n
Frequency range	2.4GHz~2.4835 GHz
Power port	Micro USB
Storage port	1pcs TF (Micro SD) storage port, max 64G
Reset port	Mater reset
Power supply and consumption	DC5V, standard1.6A
Working condition	-10C~+50C@humidity 10%~ 95% no condensation
Net weight	70.4g
Weight	229.8g
Host size	91*40mm
Packing size	110*48*180mm
APP function (English)	Support IOS/Android