

## Product Feature:

- IEEE 802.3af/at power on up to 4 ports
- Supply power to wireless access points and surveillance cameras over Cat-5 or Cat-6 cabling
- 6x 10/100 Mbps Ports with AutoUplink™
- Supports PoE power up to 15.4W for each PoE port, Max power up to 30W
- Supports PoE IEEE 802.3af/at compliant PDs
- Supports IEEE 802.3x flow control for Full-duplex Mode and back pressure for Half-duplex Mode
- Support Extend 250meters
- Internal power adapter supply



Model	VIN-POE-42N
Product Name	6-Port AF PoE Switch with 4 PoE Ports and 2 Uplink Ethernet
Connector Type	6x 10/100M copper cable RJ45 ports(4 PoE ports+2 Uplink)
Network Media	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or more UTP (≤100 meter)
Bandwidth	1.2Gbps (non-blocking)
Address Database Size	1K
MTBF	190,000 hours (about 21 years)
Forwarding Mode	Store-And-Forward
Network Protocols	IEEE 802.3i 10BASET; IEEE 802.3u 100BASETX; IEEE 802.3x Flow Control; IEEE 802.3af/at
LED Display	System: power supply; Every Port: connecting, PoE working status
Power Supply	Power input: AC100-240V 50/60Hz; (every country use a custom power plug)
PoE Ports	Port 1-4 support POE
PoE Port Power	15.4W for each POE port, Max power up to 30W
PoE Standard	IEEE 802.3af;IEEE 802.3at
PoE Feature	All ports support MDI/MDIX
Working Environment	Operating Temperature: -20 ° ~ 55 ° C; Storage Temperature: -40 ° ~ 75 ° C; Operating Humidity: 10% ~ 95%, non-condensing
Certification	CE Mark ,commercial; CE/LVD EN60950, RoHS
Radiation	CE mark, commercial; FCC Part 15 Class B; VCCI Class B; EN 55022 (CISPR 22), Class B
Transmission Distance	Data transmission distance: 100m,POE distance upto 250meters with 10M via Cat.6 or more
Size	200mm*120mm*45mm
Warranty	2 year warranty