

Product Features:

- 8*10/100Mbps PoE ports, 2*10/100/1000Mbps uplink port;
- Support IEEE802.3af/at;
- Support restrain network storm, VLAN function;
- Support Max Transmission distance up to 250m with PoE Power;
- All port supported by MDI/MDIX auto flip and self-negotiation;
- Built-in power supply;
- Maximum power of single PoE port: 30W;
- Maximum PoE power: 120W;
- Adopts store-and-forward architecture;
- Fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall;
- Support lightning protection 6000V;



Model	VIN-POE-82NGS
Power Adapter Voltage	AC 110V-240V
Consumption	120W(52V 2.3A)
PoE Ethernet Port	1-8 port:10/100Mbps
Ethernet Port	Uplink port:10/100Mbps
Transmission Distance	100Mbps:0-100m / 10Mbps:0-250m / Uplink Port:0-100m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.3ab
Switching Capacity	5.6Gbps
Packet Buffer Memory	1Mbits
Throughput	4.1664Mbps
MAC Table	2K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:148800pps/port, 1000Mbps: 148800pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	End-Span(1/2 + ; 3/6 -)
PoE Power	af=15.4w,at=30w for each port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT 100Mbps: PoE Status Indicator, Power Indicator, Extender
Working temperature	0℃~50℃
Relative Humidity	20-95%
Storage temperature	-20℃~70℃
Dimension(L*W*H)	202mm*140mm*45mm
Color & Weight	Black , 1.05Kg

Vintron Informatics Ltd. Vintron is constantly developing and improving products. We reserve the write to modify products and specification without notice.