

## Smart WiFi Camera



### Product Feature:

- H.265 video compression
- 1080p HD Enhanced Image Quality
- PTZ: Pan:355°/Tilt:110°/4x Digital Zoom.
- Two-way audio(Intercom or Hand-free)
- Motion tracking(Push 10s free video to APP)
- Motion detection(Push 6s free video to APP)
- Human-shape detection(Value-added)
- Baby crying detection(Value-added)
- Abnormal sound detection(Value-added)
- Time Hourglass, funny to share.
- Fast playback[1x,4x,8x.(16x,32x for cloud video)]
- Flexible Storage: SD card(8-64GB) /YI Cloud.
- Free APP "Yi iot" on iOS and Android.
- Free PC client, 4 cameras in one screen.

### SPECIFICATION

MODEL	VIN-PTB-10864YI-5
Processor	Mstar MSC313E
Image sensor	1/2.9" CMOS SC2232
Manual video format	MP4(1920*1080p, storage in mobile)
Video compression	H.265 HEVC
Video frame rate	Max 20 frame
Video playback mode	Mobile APP & PC client
Microphone/Speaker	Two-Way Audio, Dual Modes: Intercom/Hands-free
Built in lens	Aperture: F2.5; Focal length: FL=3.6mm
View Angle	Horizontal 80°, Vertical 50°
IR night vision effect	Dual Filter IR-Cut, 9PCS IR Leds
Minimum illumination	0.1Lux/F1.2
PTZ control	Horizontal rotation 355°, vertical 110°, 4X digital zoom.
Local storage	Support 8-64GB Micro SD card, loop recording.
Multiple protocols	TCP/IP,HTTP,TCP,UDP,DHCP,P2P etc
WiFi & Frequency	Support IEEE802.11 b/g/n; Frequency: 2.4~ 2.4835GHz
WiFi encryption	64/128-bit WEP/WPA-PSK /WPA2-PSK data encryption
Video control	Support
Smart alarm	Motion Tracking, Motion detection, Human detection, Baby crying, Abnormal sound
Alarm action	Mobile client push screenshot
Firmware upgrade	Remote upgrade can be through the network
User settings	Max 8 users online at the same time.
System interface	1 RJ45 10/100M adaptive port,1 USB power supply,1 Micro SD Card Slot
Power Supply	DC5V/2A
Power Consumption	< 5W
Working Condition	Temperature:-10℃~+50℃, Humidity 10%~ 95%
Working environment	Indoor

PAN/TILT CAMERA